

Technical Data Sheet

www.pamfast.com



**Flat Head, PAMDrive Recess,
Full Coarse Thread (8 TPI) Type 17 Point
FDYZ8200 #8 x 2" Yellow Zinc
PAM Fastening Technology, Inc.**

Head Diameter	8.00 – 8.50 mm
Major Diameter	4.10 – 4.35 mm
Min. Diameter	2.70 – 2.95 mm
Length	50.80 +-1.0 mm
Access Depth	1.65 – 2.08 mm
Wire Diameter	3.15 mm
Surface Hardness	550 – 750 mm
Core Hardness	
Breaking Torque	Min 42 (KG – CM)
Penetration	
Withdrawal	
Material	AISI 1022
Salt Spray Test (ASTM B-117)	
Bent Testing	

All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

PAM[®]

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com