



Technical Data Sheet

www.pamfast.com



**Flat Head with Sharp Nibs, PAMDrive Recess, 1/2 Coarse
Thread (8T.P.I), X-Point, 304 Stainless Steel, with Wax
IPESS10212
PAM Fastening Technology, Inc.**

Head Diameter	7.85 mm
Major Diameter	4.5-4.7 mm
Min. Diameter	3.55 mm
Length	63.5 ± 1 mm
Access Depth	1.6 - 2.0 mm
Wire Diameter	3.8 mm
Surface Hardness	550-750 HV
Core Hardness	450-240 HV
Breaking Torque	Min 38 (kg/cm)
Withdrawal/Pullout	420 pounds (2x2 fir)
Material	304 Stainless Steel
Salt Spray Test (ASTM B-117)	n/a
Bent Testing	15°

All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

PAM[®]

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com