

# Technical Data Sheet

www.pamfast.com



**Self Drilling Screw with Wings, Flat Head, PAMDrive Recess,  
Full Thread, Hardened, Zinc Plating  
SDW10134 #10-16 x 1 3/4"  
PAM Fastening Technology, Inc.**

Head Diameter	8.00 – 8.50 mm
Major Diameter	4.65 – 4.85 mm
Minor Diameter	2.70-2.95 mm
Length	50.8 +/- 1.25 mm
Access Depth	1.65 – 2.08 mm
Wire Diameter	3.80 mm
Surface Hardness	500-750 HV
Core Hardness	250 – 450 HV
Breaking Torque	min. 42 (KG/CM)
Penetration	3/4"
Withdrawal	625 LBS.
Material	AISI 1022
Salt Spray Test (ASTM B-117)	24 Hours
Bent Testing	15°

**Important Notice:** The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply. **All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.**

**PAM**<sup>®</sup>

**PAM Fastening Technology, Inc.**

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com