

# Technical Data Sheet

www.pamfast.com



**Flat Head, PAMDrive Recess, 2/3 Coarse Thread, Yellow Zinc,  
Passivation with wax  
WCYZ8134, #8 x 1 3/4"  
PAM Fastening Technology, Inc.**

|                              |                 |
|------------------------------|-----------------|
| Head Diameter                | 8.00 – 8.50 mm  |
| Major Diameter               | 4.10 – 4.35 mm  |
| Minor Diameter               | 2.95 mm         |
| Length                       | 44.45 ± 1.0mm   |
| Access Depth                 | 1.65 – 2.08 mm  |
| Wire Diameter                | 3.15 mm         |
| Surface Hardness             | 550-750 HV      |
| Core Hardness                | 450 – 240 HV    |
| Breaking Torque              | min. 42 (KG/CM) |
| Penetration                  | 3/4"            |
| Withdrawal                   | 625 LBS.        |
| Material                     | C1022           |
| Salt Spray Test (ASTM B-117) | 24 Hours        |
| Bent Testing                 | 15°             |

**All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.**

**Important Notice:** The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

**PAM®**

**PAM Fastening Technology, Inc.**

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com