


Technical Data Sheet

www.pamfast.com



**Flat Head, PAMDrive Recess, 2/3 Coarse Thread (8 T.P.I.)
WCYZ8300, #8 x 3, Yellow Zinc
PAM Fastening Technology, Inc.**

Head Diameter	8.00 – 8.50 mm
Major Diameter	4.30 – 4.70 mm
Minor Diameter	3.10 mm
Length	76.20 ± 1.0 mm
Access Depth	1.65 – 2.08 mm
Wire Diameter	3.30 mm
Surface Hardness	550 – 750 (HV)
Core Hardness	240-450 HV
Breaking Torque	Min 45 (KG – CM)
Penetration	1”
Withdrawal	650 lbs
Material	AISI 1022
Salt Spray Test (ASTM B-117)	24 hours
Bent Testing	15°

All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

PAM[®]

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com