


# Technical Data Sheet

www.pamfast.com



**Bugle head Head, PAMDrive recess, 2/3 Coarse Thread, Type-17,  
SS302, Passivation with wax  
WDSB8212 #8 x 2 1/2", SS302  
PAM Fastening Technology, Inc.**

Head Diameter	8.00 – 8.50 mm
Major Diameter	4.30 – 4.70 mm
Minor Diameter	2.7-2.90 mm
Length	63.50 ± 1.0 mm
Access Depth	1.65-2.08 mm
Wire Diameter	3.30 mm
Surface Hardness	550 – 750 HV
Core Hardness	450 – 240 HV
Breaking Torque	N/A
Penetration	1"
Withdrawal	960 LBS.
Material	STAINLESS STEEL 302
Salt Spray Test (ASTM B-117)	N/A
Bent Testing	

**All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.**

**Important Notice:** The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

**PAM**<sup>®</sup>

**PAM Fastening Technology, Inc.**

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com